

DC Volts Specifications for Fluke 16

Range 4000 mV*	Resolution: 1 mV Accuracy: 0.9% + 2
Range 4.000 V	Resolution: 0.001 V Accuracy: 0.9% + 2
Range 40.00 V	Resolution: 0.01 V Accuracy: 0.9% + 1
Range 400.0 V	Resolution: 0.1 V Accuracy: 0.9% + 1
Range 600 V	Resolution: 1 V Accuracy: 0.9% + 1

* The 4000 mV range can only be entered in manual range mode.
Use the 4000 mV range with accessories.

AC Volts Specifications

Range 4000 mV*	Resolution: 1 mV Accuracy: 1.9% + 3
Range 4.000 V	Resolution: 0.001 V Accuracy: 1.9% + 3
Range 40.00 V	Resolution: 0.01 V Accuracy: 1.9% + 3
Range 400.0 V	Resolution: 0.1 V Accuracy: 1.9% + 3
Range 600 V	Resolution: 1 V Accuracy: 1.9% + 3

* The 4000 mV range can only be entered in manual range mode.
Use the 4000 mV range with accessories.

Current (AC/DC) Specifications

Range 200 μ A	Resolution: 0.1 μ A AC Accuracy: 2% + 3 DC Accuracy: 1% + 2
-------------------	---

Ohms Specifications

Range 400.0 Ω	Resolution: 0.1 Ω Accuracy: 0.9% + 2
Range 4.000 K Ω	Resolution: 0.001 K Ω

	Accuracy: 0.9 % + 1
Range 40.00 KΩ	Resolution: 0.01 K Ω Accuracy: 0.9% + 1
Range 400.0 KΩ	Resolution: 0.1 K Ω Accuracy: 0.9% + 1
Range 4.000 MΩ	Resolution: 0.001 M Ω Accuracy: 0.9% + 1
Range 40.00 MΩ	Resolution: 0.01 M Ω Accuracy: 1.5% + 3

Capacitance Specifications*

Range 1.000 μF	Resolution: 0.001 μ F Accuracy: 1.9% + 2
Range 10.00 μF	Resolution: 0.01 μ F Accuracy: 1.9% + 2
Range 100.0 μF	Resolution: 0.1 μ F Accuracy: 1.9% + 2
Range 1000 μF	Resolution: 1.0 μ F Accuracy: 1.9% + 2
Range 10,000 μF	Resolution: 10.0 μ F Accuracy: 10% + 90 typical

* The accuracy specification is for capacitors that have negligible dielectric absorption. Capacitance measured with rc charge technique that evaluates $C = Q/V$. Capacitors with non-negligible dielectric absorption can be measured but measurement values may be in error.

Temperature Specifications*

Range 15 to 750 $^{\circ}$F	Resolution: 0.1 $^{\circ}$ F Accuracy: 1% + 1.5 $^{\circ}$ F typical
Range -40 to 15 $^{\circ}$F	Resolution: 0.1 $^{\circ}$ F Accuracy: 5% + 2.7 $^{\circ}$ F
Range -10 to 400 $^{\circ}$C	Resolution: 0.1 $^{\circ}$ C Accuracy: 1% + 0.8 $^{\circ}$ C typical
Range -40 to 10 $^{\circ}$C	Resolution: 0.1 $^{\circ}$ C Accuracy: 5% + 1.5 $^{\circ}$ C

* Temperature accuracy specifications do not include the error of the thermocouple.

Safety

600V ac/dc	Maximum voltage between any terminal and earth ground. Conforms to the requirements of IEC-1010-1, 1990-09 and ANSI/ISA-S82.01-94 for use in Overvoltage Category III locations. Make ac or dc voltage measurements on electrical distribution systems to 600V where transients do not exceed 6 kV and only on circuits limited to 14 kVA if the circuit voltage rating is above 250V.
Certification agencies (approvals/listings pending)	UL Per standard UL 3111 CSA Per standard CSA/CAN C22.2 No.1010.1-92 TsV Per standard EN61010 Part 1-1993
Drop test	ANSI/ISA-S82.01-94 and EN61010 Part1-1993. 10 ft. drop to hardwood on concrete

General Specifications

Size	(HxWxL) 1.12" x 2.95" x 6.55", (2.8 cm x 7.5 cm x 16.6 cm)
Battery life	650 hours with Alkaline
Weight	12 oz (340g)
Warranty	Three years