


Above: 6023A, 6028A
Below: 6010A, 6011A, 6012A and 6015A



Above: 6033A and 6031A (Option 001 on right)
Below: 6030A, 6031A, 6032A, and 6035A

Abbreviated Specifications and Characteristics

System Autorangers (GPIB)		6030A	6031A	6032A	6033A	6035A	6038A	
Autorangers (w/o GPIB)		6010A	6011A	6012B	6023A	6015A	6028A	
Output ratings	Voltage	0 to 200 V	0 to 20 V	0 to 60 V	0 to 20 V	0 to 500 V	0 to 60 V	
	Current	0 to 17 A	0 to 120 A	0 to 50 A	0 to 30 A	0 to 5 A	0 to 10 A	
Maximum power	Watts	1,200 W	1,072 W	1,200 W	240 W	1,050 W	240 W	
Autoranging output	V1, P1	200 V, 5 A	20 V, 50 A	60 V, 17.5 A	20 V, 10 A	500 V, 2 A	60 V, 3.3 A	
	V2, P2	120 V, 10 A	14 V, 76 A	40 V, 30 A	14 V, 17.2 A	350 V, 3 A	40 V, 6 A	
	V3, P3	60 V, 17 A	7 V, 120 A	20 V, 50 A	6.7 V, 30 A	200 V, 5 A	20 V, 10 A	
Programming accuracy (at 25° C ±5° C) System models only	Voltage	0.035% +145 mV	0.035% +15 mV	0.035% +40 mV	0.035% +9 mV	0.25% +400 mV	0.035% +40 mV	
	Current	0.2% +25 mA	0.25% +250 mA	0.2% +85 mA	0.15% +20 mA	0.3% +63 mA	0.09% +10 mA	
Ripple and noise , (20 Hz to 20 MHz)	Voltage	rms	22 mV	8 mV	5 mV	3 mV	50 mV	3 mV
		p-p	50 mV	50 mV	40 mV	30 mV	160 mV	30 mV
	Current	rms	15 mA	120 mA	25 mA	30 mA	50 mA	5 mA
Readback accuracy (at 25° C ±5° C) System models only	Voltage	0.08% + 80 mV	0.08% +7 mV	0.08% +20 mV	0.07% +6 mV	0.5% +200 mV	0.07% +50 mV	
	Current	0.36% +15 mA	0.4% +100 mA	0.36% +35 mA	0.3% +25 mA	0.5% +50 mA	0.2% +11 mA	
Load regulation	Voltage	0.01%+	5 mV	3 mV	5 mV	2 mV	40 mV	3 mV
	Current	0.01%+	10 mA	15 mA	10 mA	9 mA	.03+34 mA	5 mA
Line regulation System models only	Voltage	0.01%+	5 mV	2 mV	3 mV	1 mV	13 mV	2 mV
	Current	0.01%+	5 mA	25 mA	10 mA	6 mA	.03+17 mA	2 mA
Transient response time 10% step change	Time	2 ms	2 ms	2 ms	1 ms	5 ms	1 ms	
	Level	150 mV	100 mV	100 mV	50 mV	200 mV	75 mV	
dc floating voltage (either terminal can be grounded or floated from chassis ground)		±550 V	±240 V	±240 V	±240 V	±550 V	±240 V	
ac input current	100 Vac (system only)	24 A	24 A	24 A	6.0 A	24 A	6.0 A	
	120 Vac	24 A	24 A	24 A	6.5 A	24 A	6.5 A	
	220 Vac	15 A	15 A	15 A	3.8 A	15 A	3.8 A	
	240 Vac	14 A	14 A	14 A	3.6 A	14 A	3.6 A	
Weight	Net	16.3 kg (36 lb)	16.3 kg (36 lb)	16.3 kg (36 lb)	9.6 kg (21 lb)	16.3 kg (36 lb)	9.6 kg (21 lb)	
	Shipping	21.7 kg (48 lb)	21.7 kg (48 lb)	21.8 kg (48 lb)	11.4 kg (25 lb)	21.7 kg (48 lb)	11.4 kg (25 lb)	
Price	System Autorangers (GPIB)	6030A/ \$4,201	6031A/ \$4,201	6032A/ \$4,201	6033A/ \$3,151	6035A/ \$4,626	6038A/ \$3,151	
	Autorangers (w/o GPIB)	6010A/ \$3,555	6011A/ \$3,555	6012B/ \$3,555	6023A/ \$2,505	6015A/ \$3,974	6028A/ \$2,505	

Remote Sensing: Up to 2 V drop in each lead. Voltage regulation degrades for greater than 0.5 V drop.

Regulatory Compliance: Listed to UL-1244; certified to CSA 556B; complies with EN 61010-1, carries the CE mark

RFI Suppression: Complies with CISPR-11, Group 1, Class A

Inductive Load: 6023A, 6028A are stable in CC mode for loads up to 1 H. 6010A–6012B, 6015A are stable in CC mode for loads up to 100 mH.

Size: 6030A–32A, 6035A: 132.6 mm H x 425.5 mm W x 503.7 mm D (5.25 in x 16.75 in x 19.83 in).

6033A, 6038A, 6023A, 6028A: 177.0 mm H x 212.3 mm W x 516.4 mm D (6.97 in x 8.36 in x 17.87 in).

6010A–12B, 6015A: 132.6 mm H x 425.5 mm W x 516.4 mm D (5.25 in x 16.75 in x 20.33 in).

6010A–12B, 6015A: 132.6 mm H x 425.5 mm W x 516.4 mm D (5.25 in x 16.75 in x 20.33 in).

Key Literature

2000/01 Agilent Technologies Power Products Catalog, p/n 5968-2199E

For more information, visit our web site:

<http://www.agilent.com/find/autorangingPS>

Ordering Information

Standard: 104 to 127 VAC, 48 to 63 Hz

Opt 001 Front panel has only line switch, line indicator, and OVP adjust (6030A–33A and 6038A only)

Opt 002 Provides extra programming and monitoring capabilities (6010A–12B, 6023A, 6028A only) **+\$418**

Opt 100 87 to 106 Vac, 48 to 63 Hz (power supply output is derated to 75%) 6030A–33A, 6035A, 6038A only **\$0**

Opt 220 191 to 233 Vac, 48 to 63 Hz **\$0**

Opt 240 209 to 250 Vac, 48 to 63 Hz **\$0**

Opt 800 Rackmount Kit for Two Half-rack Units Side by Side. p/n 5061-9694 and 5062-3978 **+\$86**

Opt 908 Rackmount Kit for a Single Half-rack Unit Models 6023A, 6028A, 6033A and 6038A (with blank filler panel); p/n 5062-3960 **+\$84**

Models 6010A–12B, 6015A, 6030A–32A and 6035A; p/n 5062-3977 **+\$42**

Opt 909 Rackmount Kit with Handles. For 6010A–12B, 6015A, 6030A–32A, 6035A; p/n 5062-3983 **+\$94**

Opt 910 Service Manual and extra Operating Guide For Models 6010A–12B, 6015A, 6023A, 6028A **+\$37**

For Models 6030A–33A, 6035A, 6038A **+\$37**

A line cord option must be specified for 6010A–12B, 6015A, 6030A–32A, 6035A. See page 191 for ordering information.

Accessories
5080-2148 Serial Link Cable, 2 m (6.6 ft) for 6030A, 6031A, 6031A, 6032A, 6033A, 6035A, and 6038A **\$14**

1494-0060 Rack Slide Kit **\$120**

Price

-\$306