

# TekConnect® Adapters

▶ TCA75 • TCA-BNC • TCA-SMA • TCA-N



## TekConnect Interface Delivers Superior Signal Fidelity, Unparalleled Versatility and Ease-of-Use

Tektronix award-winning TDS7000, CSA7000 and TDS6000 Series oscilloscopes allow engineers to make high-speed measurements quickly and efficiently. In addition to these high-speed measurements, many of today's designers also face the challenges of measuring high voltage, current, power or even micro-volt level signals to gain a more complete understanding of their designs.

The TekConnect interface ensures superior signal fidelity with useful bandpass up to 18 GHz at the oscilloscope input, while offering unparalleled versatility with the world's widest

array of accessory signal acquisition solutions for high-performance, real-time oscilloscopes. This interface delivers a more robust oscilloscope interface for next-generation products with multi-GHz analog bandwidths, overcoming many of the inherent bandwidth limitations of BNC-based interfaces. The TekConnect interface preserves a low voltage standing wave ratio (VSWR) 50  $\Omega$  environment as well as a reliable electrical connection. A convenient, one-button release and locking mechanism provides quick, easy installation and removal of probes, amplifiers and adapters.

## ▶ Features & Benefits

### TCA75 – TekConnect®-to-75 $\Omega$ BNC

- DC to  $\geq 4$  GHz (Instrument Dependent)
- VSWR – 1.1:1 (26.45 dB)
- 75  $\Omega$  Input
- Auto Attenuation Factor Correction

### TCA-BNC – TekConnect-to-TEKPROBE™ BNC 50 $\Omega$

- DC to  $\geq 4$  GHz (Instrument Dependent)
- 50  $\Omega$  Input (Only)
- Probe Control TEKPROBE BNC (50  $\Omega$ )

### TCA-SMA – TekConnect-to-SMA

- DC to  $\geq 18$  GHz (Instrument Dependent)
- 50  $\Omega$  Input (Only)

### TCA-N – TekConnect-to-N

- DC to  $\geq 11$  GHz (Instrument Dependent)
- 50  $\Omega$  Input (Only)

## ▶ Applications

Signal Integrity, Jitter and Timing Analysis

Verification, Characterization and Debug of Sophisticated Designs

High-speed Digital Devices and Circuits

Power Supplies/Inverters

Semiconductor Devices

Electronic Ballasts

Industrial/Consumer Electronics

Mobile Communications

Motor Drives

Transportation Systems

Disk Drive Analysis

Investigation of Transient Phenomena

Spectral Analysis

Video Design and Development

- HDTV and Streaming Digital Video

COMPUTING

COMMUNICATIONS

VIDEO

## TekConnect® Adapters

► TCA75 • TCA-BNC • TCA-SMA • TCA-N

### TekConnect TCA Series Adapters Expand the Functionality of Tektronix High-performance Oscilloscopes

This family of adapter systems provides less signal distortion and better performance than traditional connections used to move a signal from one environment to another, such as BNC to N or BNC to SMA.

#### TCA75 Adapter (75 to 50 Ω)

The TCA75 adapter allows Tektronix oscilloscopes with TekConnect interface to easily access and measure 75 Ω terminated circuitry. The TCA75's attenuation factor is automatically corrected to provide the end user with correctly displayed signal magnitudes.

#### TCA-BNC Adapter (50 Ω only)

A direct 50 Ω input with TEKPROBE BNC 50 Ω capability, this adapter may be used as a direct 50 Ω BNC input or with Tektronix high-speed active and differential probes requiring the TEKPROBE BNC 50 Ω interface.

#### TCA-SMA and TCA-N Adapters (only)

The high-speed SMA and N type adapters allow a more direct connection to the signal under test requiring N or SMA connections without losing performance by adding other external conversion adapters.

### ► Characteristics

Model Specification	TCA75	TCA-BNC	TCA-SMA	TCA-N
Attenuation Accuracy at DC	2.46X ±1.5%	Refer to Host Instrument Specification		
Input Impedance	75 Ω ±1.5%	50 Ω	50 Ω	50 Ω
<b>Typical</b>				
Bandwidth (-3 dB)	DC to 4 GHz (Adapter Only)	DC to 4 GHz (Maximum Frequency) (Limited By Host Instrument)	DC to ≥18 GHz (Maximum Frequency) (Limited By Host Instrument)	DC to ≥11 GHz (Maximum Frequency) (Limited By Host Instrument)
Propagation Delay (Input-to-Output)	<200 ps			
RMS Noise	Refer to Host Instrument Specification			
VSWR (Return Loss)	1.1:1 (26.45 dB)	1.15:1 (23.13 dB)	1.05:1 + 0.01 x F (in GHz) (32.25 dB)	1.3:1 (17.7 dB)
RF Insertion Loss	6.05 dB (Adapter Only)	0.25 dB Max (Adapter Only)	0.06*SQRT F (GHz) (Adapter Only)	0.3 dB Max (Adapter Only)
Rise Time	<100 ps* <sup>1</sup> (Minimum Rise Time) (Limited By Host Instrument)	≤100 ps (Minimum Rise Time) (Limited By Host Instrument)	≤22 ps (Minimum Rise Time) (Limited By Host Instrument)	≤36 ps (Minimum Rise Time) (Limited By Host Instrument)
Maximum Input Voltage (Derated with Frequency)	≤12 V DC or ≤12 V <sub>RMS</sub> (2 W Max.)	Refer to Host Instrument Specification		
<b>Nominal</b>				
Inputs	1 (BNC 75 Ω)	1 (TEKPROBE™ BNC 50 Ω)	1 (SMA 50 Ω)	1 (N 50 Ω)
Adapter Model Compatibility	Refer to TekConnect® Amplifier, Adapters and Probes Compatibility Table			
Warranty	1 Year			

\*<sup>1</sup> Calculated Small Signal  $t_r = 0.4/F_3$  dB.

**▶ TekConnect® Amplifier, Adapters and Probes Compatibility<sup>2</sup>**

Accessory Type	Oscilloscope			TekConnect Amplifiers, Adapters and Probes				
	TDS6000B TDS/CSA7000B TekConnect Series							
	6 GHz 8 GHz	4 GHz	1.5 GHz 2.5 GHz	TCA-1MEG High Impedance Buffer Amplifier (P6139A Included)	TCA-BNC Adapter (Standard with w/TDS7154/TDS7254/CSA7154)	TCA-SMA Adapter (Standard with TDS7404/CSA7404)	TCA-N Adapter	TCA75 Adapter
Instrument Input Connection	TekConnect Interface			TEKPROBE™ BNC 1 MΩ-to-TekConnect Interface	TEKPROBE BNC 50 Ω-to-TekConnect Interface	SMA-to-TekConnect Interface	N-to-TekConnect Interface	75 to 50 Ω TekConnect Adapter
Instrument Input Impedance	TekConnect Interface Probes, Amplifier and Adapter Dependent			1 MΩ/10 pF	50 Ω	50 Ω	50 Ω	50 Ω
Passive Voltage Probes (1X)	P6101B w/TCA-1MEG			P6101B	N/A	N/A	N/A	N/A
Passive Voltage Probes (10X)	P6139A w/TCA-1MEG			P6139A	N/A	N/A	N/A	N/A
50 Ω Divider Voltage Probes	P6150 w/TCA-SMA P6158 w/TCA-BNC			N/A	P6158	P6150	N/A	N/A
Active Voltage Probes General	P6245 w/TCA-BNC P6243 w/TCA-BNC			N/A	P6245 P6243	N/A	N/A	N/A
Active Voltage Probes >2 GHz	P7260 <sup>3</sup> , P7240 <sup>3</sup> P6249 w/TCA-BNC P6241 w/TCA-BNC		P7225 <sup>3</sup> , P7240 <sup>3</sup> P6249 w/TCA-BNC P6241 w/TCA-BNC	N/A	P6249 P6241	N/A	N/A	N/A
Differential Voltage Probes >2 GHz	P7380 <sup>3</sup> P7380SMA <sup>3</sup> P7350 <sup>3</sup> P7350SMA <sup>3</sup> P6330 w/TCA-BNC	P7380 <sup>3</sup> P7380SMA <sup>3</sup> P7350 <sup>3</sup> P7350SMA <sup>3</sup> P7330 <sup>3</sup> P6330 w/TCA-BNC	P7350 <sup>3</sup> P7350SMA <sup>3</sup> P7330 <sup>3</sup> P6330 w/TCA-BNC	N/A	P6330	N/A	N/A	N/A
Differential Voltage Probes <1.8 GHz <8 V Logic	P6248 w/TCA-BNC P6247 w/TCA-BNC P6246 w/TCA-BNC			N/A	P6248 P6247 P6246	N/A	N/A	N/A
Differential Voltage Probes Micro-volt	ADA400A w/TCA-1MEG			ADA400A	N/A	N/A	N/A	N/A
High Voltage Probes Differential	P5205 w/TCA-1MEG P5210 w/TCA-1MEG			P5205 P5210	N/A	N/A	N/A	N/A
High Voltage Probes Single-ended	P5100 w/TCA-1MEG P6015A w/TCA-1MEG			P5100	N/A	N/A	N/A	N/A
Current Probe AC/DC <15 A	TCP202 w/TCA-BNC			N/A	TCP202	N/A	N/A	N/A
Current Probe AC/DC 5 mA to 20 A	TCP300/TCP400/AM5030S w/TCA-BNC			TCP300/TCP400/AM5030S	TCP300/TCP400/AM5030S	N/A	N/A	N/A
Current Probe AC High Frequency	CT6 w/TCA-BNC CT1 w/TCA-BNC			N/A	CT6 CT1	N/A	N/A	N/A
Current Probe AC Low Frequency	P6021 w/TCA-1MEG P6022 w/TCA-1MEG			P6021 P6022	N/A	N/A	N/A	N/A
O/E Converter Probes	P6701B w/TCA-BNC P6703B w/TCA-BNC			N/A	P6701B P6703B	N/A	N/A	N/A

<sup>2</sup> Firmware version 2.1 or greater required for all referenced oscilloscopes.

<sup>3</sup> P7225, P7240, P7260, P7330, P7350SMA, P7380 and P7380SMA are high-speed active and differential probing solutions for Tektronix oscilloscopes with TekConnect interface. These probes require no other adapters.

# TekConnect® Adapters

▶ TCA75 • TCA-BNC • TCA-SMA • TCA-N

## ▶ Ordering Information

**TCA75** – TekConnect®-to-75 Ω Adapter.

**TCA-BNC** – TekConnect-to-BNC Adapter.

**TCA-SMA** – TekConnect-to-SMA Adapter.

**TCA-N** – TekConnect-to-N Adapter.

All Include: Instruction Manual and Certificate of Compliance.

## Recommended Accessories

### Passive Voltage Probes

**P6150** – (Use with TCA-SMA), 9 GHz, 1X/10X, 50 Ω divider probe.

**P6158** – (Use with TCA-BNC), 3 GHz, 20X, 50 Ω divider probe.

### High Speed Active Voltage Probes

**P6205** – (Use with TCA-BNC), 750 MHz, 10X, <2 pF/10 MΩ.

**P6243** – (Use with TCA-BNC), 1 GHz, 10X, <1 pF/1 MΩ.

**P6245** – (Use with TCA-BNC), 1.5 GHz, 10X, <1 pF/1 MΩ.

**P6249** – (Use with TCA-BNC), 4 GHz, 5X, <1 pF/20 kΩ.

**P6241** – (Use with TCA-BNC), 4 GHz, 10X, <0.5 pF/40 kΩ.

### High Speed Active Differential Voltage Probes

**P6247** – (Use with TCA-BNC), 1 GHz, 1X/10X, <1 pF/200 kΩ differential.

**P6248** – (Use with TCA-BNC), 1.5 GHz, 1X/10X, <1 pF/200 kΩ differential.

**P6330** – (Use with TCA-BNC), 3.5 GHz, 1X/10X, <1 pF/200 kΩ differential.

## Electrical Communication Adapters

**AMT75** – (Use with TCA-BNC), 75 Ω to 50 Ω Video Adapter.

**AFTDS** – (Use with TCA-BNC), Differential Communications Adapter.

## Current Measurement Tools

**TCP202** – (Use with TCA-BNC), AC/DC, 20 Amps, TEKPROBE™ Interconnect Current Probe 20 Amps.

**AM503S** – (Use with TCA-BNC), AC/DC, 5 mA to 700 Amp, Current Amplifier Measurement System. (Extended Current Capability by ordering additional Current Probes).

**CT-1** – (Use with TCA-BNC), 1 GHz, AC Current Transformer.

**CT-2** – (Use with TCA-BNC), 200 MHz, AC Current Transformer.

**CT-6** – (Use with TCA-BNC), 2 GHz, AC Current Transformer.

## Cables and Terminations

**012-0057-01** – (Use with TCA-BNC), 50 Ω BNC to BNC coaxial cable.

**012-0482-00** – (Use with TCA-BNC), 50 Ω BNC to BNC coaxial cable, precision 1%, male-to-male.

**011-0049-02** – (Use with TCA-BNC), 50 Ω feed through termination.

## Contact Tektronix:

**ASEAN / Australasia / Pakistan** (65) 6356 3900

**Austria** +43 2236 8092 262

**Belgium** +32 (2) 715 89 70

**Brazil & South America** 55 (11) 3741-8360

**Canada** 1 (800) 661-5625

**Central Europe & Greece** +43 2236 8092 301

**Denmark** +45 44 850 700

**Finland** +358 (9) 4783 400

**France & North Africa** +33 (0) 1 69 86 80 34

**Germany** +49 (221) 94 77 400

**Hong Kong** (852) 2585-6688

**India** (91) 80-22275577

**Italy** +39 (02) 25086 1

**Japan** 81 (3) 6714-3010

**Mexico, Central America & Caribbean** 52 (55) 56666-333

**The Netherlands** +31 (0) 23 569 5555

**Norway** +47 22 07 07 00

**People's Republic of China** 86 (10) 6235 1230

**Poland** +48 (0) 22 521 53 40

**Republic of Korea** 82 (2) 528-5299

**Russia, CIS & The Baltics** +358 (9) 4783 400

**South Africa** +27 11 254 8360

**Spain** +34 (91) 372 6055

**Sweden** +46 8 477 6503/4

**Taiwan** 886 (2) 2722-9622

**United Kingdom & Eire** +44 (0) 1344 392400

**USA** 1 (800) 426-2200

**USA** (Export Sales) 1 (503) 627-1916

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Last Update March 01, 2004

Our most up-to-date product information is available at:  
[www.tektronix.com](http://www.tektronix.com)

Product(s) are manufactured  
in ISO registered facilities.



Copyright © 2004, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

06/04 HB/WOW

60W-14970-4