



5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)821-7413  
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

**MODEL 7004**  
**20 - 2000 MHz**  
**22 WATTS**  
**BANDED POWER RF AMPLIFIER**

**Solid State  
 Broadband High  
 Power RF Amplifier**

The 7004 is a 20W multi channel broadband system that covers the 20 – 2000 MHz frequency range with a single RF input and Single RF output port.

The system includes RF high power switches controlled by the system controller. The RS232/ Ethernet and/or Front panel key-pad provides full control and reduces the power consumption to the minimum by shutting down the un-selected channel. The System is configured in a Rear panel Connectors configuration.

	<u>Parameter</u>	<u>Specification @ 25° C</u>
<b><u>Electrical</u></b>		
1	Frequency Range	20 – 2000 MHz
2	Saturated Power Output	20 Watts typ.
3	Nominal RF drive for rated power	0 dB typ.
4	Small Signal Flatness	+/-2dB
5	Power Output @ P1dB	10 Watts min @ 20 to 1000 MHz 10 Watts typ. @ 1 to 2 GHz
6	Input VSWR	2:1 max
7	Harmonics	-15 dBc typ. @ 20 to 1000 MHz -20 dBc typ. @ 1 to 3 GHz
8	Spurious Signals	> -60 dBc typical
9	Temperature Protection	Baseplate above 80° C
10	AC Power Consumption (only one channel transmit at the time)	250 Watt @ 20 to 1000 MHz 500 Watts @ 1 to 3 GHz
11	AC Power Input	100-240VAC, 1Ø single Phase
12	Noise Figure	10dBm max
13	Maximum RF Input	10 dBm max for 10 sec
14	Antenna Switching time	50mS max
<b><u>Mechanical</u></b>		
15	Dimensions	19" x 26" x 5.25"
16	Weight	50 lb. max
17	Connectors	Type-N
18	Grounding	Chassis
19	Cooling	Internal Forced Air
<b><u>Environmental</u></b>		
20	Operating Temperature	0° C to +50° C
21	Operating Humidity	95% Non-condensing
22	Operating Altitude	Up to 10,000' Above Sea Level
23	Shock and Vibration	Normal Truck transport

Specifications subject to change without notice






5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)577-9887  
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

**MODEL 7004**

**20 - 2000 MHz**  
**20 WATTS**  
**BANDED POWER RF AMPLIFIER**



**CIRCUIT PROTECTIONS**

- ◇ Protection against VSWR of > 2:1 latched with Reset
- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

**CONTROL & INDICATIONS**

- ◇ AC Circuit Breaker
- ◇ Band Select
- ◇ Forward power of selected channel
- ◇ Reflected Power of selected channel
- ◇ VSWR Fault Reset

