

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

ъ.

MODEL 4041

2 - 30 MHz 300 WATTS LINEAR POWER RF AMPLIFIER

Solid State **Band-specific High Power RF Amplifier**

The 4041 is a 300 Watt band-specific amplifier that covers the 2 - 30 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and comamplifier ponents, this achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4041 comes with an extended multiyear warranty.

| | Parameter | Specification @ 25 °C |
|----------------------|----------------------------|--|
| Electrical | | |
| 1 | Frequency Range | 2 – 30 MHz |
| 2 | Saturated Output Power | 300 Watts typical |
| 3 | Power Output @ 1dB Comp. | 200 Watts min |
| 5 | Small Signal Gain | +56 dB min |
| 6 | Small Signal Gain Flatness | ± 2.0 dB max |
| 7 | IP ₃ | +59 dBm typical |
| 8 | Input VSWR | 2:1 max |
| 9 | Harmonics | -15 dBc typical @ 200 Watts |
| 10 | Spurious Signals | > -60 dBc typical @ 200 Watts |
| 11 | Input/Output Impedance | 50 Ohms nominal |
| 12 | AC Input Power | 1200 Watts max |
| 13 | AC Input | 100 – 240 VAC, single phase |
| 14 | RF Input | 0 dBm max. |
| 15 | RF Input Signal Format | CW/AM/FM/PM/Pulse |
| 16 | Class of Operation | AB |
| <u>Mechanical</u> | | |
| 17 | Dimensions | 19" x 5.25" x 20" |
| 18 | Weight | 50 lb. max |
| 19 | Connectors | Type-N |
| 20 | Grounding | Chassis |
| 21 | Cooling | Internal Forced Air |
| <u>Environmental</u> | | |
| 22 | Operating Temperature | 0° C to +50° C |
| 23 | Operating Humidity | 95% Non-condensing |
| 24 | Operating Altitude | Up to 10,000' Above Sea Level |
| 25 | Shock and Vibration | Normal Truck Transport Specifications subject to change without notice. |

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ◊ Over Voltage

ORDERING MODELS

- ♦ R - Rear Panel Connectors
- ♦ F - Front Panel Connectors
- ♦ RE R model w/Control Option
- ♦ FE F model w/Control Option
- ♦ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface



FE Model Shown

| Approved By: Date: | |
|--------------------|--|
|--------------------|--|