

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## **MODEL 4064**

## 1.8 - 2.5 GHz 60 WATTS LINEAR POWER RF AMPLIFIER

## Solid State Band-Specific High Power RF Amplifier

The 4064 is a 60 Watt broadband amplifier that covers the 1.8 - 2.5 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 4064 comes with an extended multiyear warranty.

## **CIRCUIT PROTECTIONS**

- **Overload**
- Over Current
- ◊ Over Voltage

<b>ORDERING MODELS</b>	NG MODELS
------------------------	-----------

- ◊ F Front Panel Connectors
- RE R model w/Control Option
- ♦ FE F model w/Control Option
- ◊ RT RE model w/Ethernet Interface
- ◊ FT FE model w/Ethernet Interface

Approved By:

	Parameter	Specification @ 25° C
<b>Electrical</b>		
1	Frequency Range	1.8 – 2.5 GHz
2	Saturated Output Power	60 Watts typical
3	Power Output @ 1dB Comp.	50 Watts min
4	Small Signal Gain	+49 dB min
5	Small Signal Gain Flatness	<u>+</u> 1.0 dB max
6	IP <sub>3</sub>	+57 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 50 Watts
9	Spurious Signals	> -60 dBc typical @ 50 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	600 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	+10 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	A/AB
Mechanical		
16	Dimensions	19" x 5.25" x 20"
17	Weight	48 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
Environmental		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.

