

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4062

1.85 - 2.17 GHz **60 WATTS** LINEAR POWER RF AMPLIFIER

Solid State Band-specific High Power RF Amplifier

The 4062 is a 60 Watt band-specific amplifier that covers the 1.85-2.17 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4062 comes with an extended multiyear warranty.

	<u>Parameter</u>	Specification @ 25° C		
<u>Electrical</u>				
1	Frequency Range	1.85 – 2.17 GHz		
2	Saturated Output Power	60 Watts typical		
3	Power Output @ 1dB Comp.	45 Watts min		
4	Small Signal Gain	+50 dB min		
5	Small Signal Gain Flatness	<u>+</u> 0.75 dB max		
6	IP ₃	+56 dBm typical		
7	Input VSWR	2:1 max		
8	Harmonics	-20 dBc typical @ 45 Watts		
9	Spurious Signals	> -60 dBc typical @ 45 Watts		
10	Input/Output Impedance	50 Ohms nominal		
11	AC Input Power	250 Watts max		
12	AC Input	100 – 240 VAC, single phase		
13	RF Input	+10 dBm max		
14	RF Input Signal Format	CW/AM/FM/PM/Pulse		
15	Class of Operation	A/AB		
<u>Mechanical</u>				
16	Dimensions	19" x 3.5" x 18"		
17	Weight	36 lb. max		
18	Connectors	Type-N		
19	Grounding	Chassis		
20	Cooling	Internal Forced Air		
Environmental				
21	Operating Temperature	0° C to +50° C		
22	Operating Humidity	95% Non-condensing		
23	Operating Altitude	Up to 10,000' Above Sea Level		
24	Shock and Vibration	Normal Truck Transport Specifications subject to change without notice.		

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ♦ Over Voltage

ORDERING MODELS

- ♦ R - Rear Panel Connectors
- ♦ F - Front Panel Connectors
- ♦ RE R model w/Control Option
- ♦ FE F model w/Control Option
- ♦ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface



RE Model Shown

Approved By:	Date:	