



# Agilent E1406A VXI GPIB Command Module C-Size

## Data Sheet



### Features

- **1-Slot, C-size, message-based commander**
- **GPIB, RS-232, Slot 0, and Resource Manager**
- **2 MB RAM**
- **MXIbus protocol support for high throughput**
- **Easy to program as message-based instruments**

### Description

The Agilent Technologies E1406A Command Module is a C-size, 1-slot VXI message-based commander that provides Slot 0 and Resource Manager functions. It can act as a VMEbus system controller and GPIB (IEEE-488)-to-VXIbus interface device for transparently communicating with any manufacturer's message-based VXI modules. The E1406A Command Module has FLASH memory for downloadable drivers, so you can program Agilent register-based devices using the high-level SCPI programming language. It also translates SCPI commands for register-based instruments and therefore,

makes these VXI devices as easy to program as message-based instruments.

This command module also includes a MXIbus Resource Manager for VXIbus extensions. This allows you to maintain high-throughput performance in multiple mainframe systems. With its flexible triggering and clock interfacing, you can synchronize the VXI backplane 10 MHz clock to an external TTL signal.

Refer to the Agilent Technologies Website for instrument driver availability and downloading instructions, as well as for recent product updates, if applicable.



## Product Specifications

---

### General Characteristics

Processor:	16 MHz 68000
Interface:	IEEE-488
Clock accuracy:	0.005% elapsed time
Memory:	1.75 MB FLASH max. 2 MB RAM max.
Shared memory:	512 kB max.
Agilent IBasic:	Yes
Slot 0 functions:	Yes
Resource manager:	Yes
MXIbus resource manager:	Yes
CLK10:	Yes
Temperature coefficient:	0.001%, to 0.012% of time since last set (per °C change in temperature)
Resolution:	1.0 s

---

### CLK10

Input:	TTL or low-level ac
Minimum input level:	40 mV p-p
Maximum input level:	42.5 V p-p
Output:	TTL
Jitter:	0.03% (-55 db)
Initial accuracy:	50 ppm
Maximum stability:	± 20 ppm/year (0-55 °C)
Typical stability:	± 3 ppm/year at 25 °C

---

### Trigger Input

Levels:	TTL
Input load:	55 kΩ, 50 pF
Maximum rate:	12.5 MHz (TTL), 40 MHz (ECL)
Minimum pulse width:	30 ns (TTL), 12.5 ns (ECL)
Maximum trigger delay:	30 ns

---

### RS-232 Interface (for terminal only)

Baud rate:	300, 1200, 2400, 4800, 9600, 19200
Parity:	Even, Odd, One, Zero, None
Character size:	7, 8
Pace:	Xon/Xoff, None
Hardware handshake:	DTR, RTS
Buffer size:	16 characters
RS-232 terminals supported:	HP 700/92, HP 700/94, HP 700/22, HP 700/43; WYSE WY-30, DEC VT100, DEC VT220
VXI compliance:	Revision 1.4 compliance

## General Specifications

### VXI Characteristics

VXI device type:	Message-based commander
Size:	C
Slots:	1
Connectors:	P1/2
Shared memory:	Yes
VXI buses:	Local bus A, TTL Trigger Bus, ECL Trigger Bus

### Instrument Drivers:

See the Agilent Technologies Website for driver availability and downloading.

[http://www.agilent.com/find/inst\\_drivers](http://www.agilent.com/find/inst_drivers)

Command module firmware:	n/a
Command module firmware rev:	n/a
I-SCPI Win 3.1:	n/a
I-SCPI Series 700:	n/a
C-SCPI LynxOS:	n/a
C-SCPI Series 700:	n/a
Panel Drivers:	Yes
VXIplug&play Win Framework:	Yes
VXIplug&play Win95/NT Framework:	Yes
VXIplug&play HP-UX Framework:	No

### Module Current

	$I_{PM}$	$I_{DM}$
+5 V:	3.2 A	0.32 A
+12 V:	.01 A	.01 A
-12 V:	.01 A	.01 A
+24 V:	.03 A	.003 A
-24 V:	0	0
-5.2 V:	.4 A	.04 A
-2 V:	.01 A	.01 A

### Cooling Slot

Watts/slot:	19.00
$\Delta P$ mm H <sub>2</sub> O:	0.30
Air flow liter/s:	1.50

## Ordering Information

Description	Product No.
VXI GPIB Command Module, C-size	E1406A
Service manual	E1406A OB3
Taiwan - Chinese localization	E1406A AB0
Korea - Korean localization	E1406A AB1
Germany - German localization	E1406A ABD
Spain - Spanish localization	E1406A ABE
France - French localization	E1406A ABF
Japan - Japanese localization	E1406A ABJ
Italy - Italian localization	E1406A ABZ



### Agilent Email Updates

[www.agilent.com/find/emailupdates](http://www.agilent.com/find/emailupdates)  
Get the latest information on the products and applications you select.



### Agilent Direct

[www.agilent.com/find/agilentdirect](http://www.agilent.com/find/agilentdirect)  
Quickly choose and use your test equipment solutions with confidence.



### Agilent Open

[www.agilent.com/find/open](http://www.agilent.com/find/open)  
Agilent Open simplifies the process of connecting and programming test systems to help engineers design, validate and manufacture electronic products. Agilent offers open connectivity for a broad range of system-ready instruments, open industry software, PC-standard I/O and global support, which are combined to more easily integrate test system development.



### LXI

[www.lxistandard.org](http://www.lxistandard.org)  
LXI is the LAN-based successor to GPIB, providing faster, more efficient connectivity. Agilent is a founding member of the LXI consortium.

## Remove all doubt

Our repair and calibration services will get your equipment back to you, performing like new, when promised. You will get full value out of your Agilent equipment throughout its lifetime. Your equipment will be serviced by Agilent-trained technicians using the latest factory calibration procedures, automated repair diagnostics and genuine parts. You will always have the utmost confidence in your measurements.

Agilent offers a wide range of additional expert test and measurement services for your equipment, including initial start-up assistance onsite education and training, as well as design, system integration, and project management.

For more information on repair and calibration services, go to:

[www.agilent.com/find/removealldoubt](http://www.agilent.com/find/removealldoubt)

## www.agilent.com

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

### Americas

Canada	(877) 894-4414
Latin America	305 269 7500
United States	(800) 829-4444

### Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Thailand	1 800 226 008

### Europe & Middle East

Austria	0820 87 44 11
Belgium	32 (0) 2 404 93 40
Denmark	45 70 13 15 15
Finland	358 (0) 10 855 2100
France	0825 010 700* <small>*0.125 € fixed network rates</small>
Germany	01805 24 6333** <small>**0.14 €/minute</small>
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
Switzerland (French)	41 (21) 8113811(Opt 2)
Switzerland (German)	0800 80 53 53 (Opt 1)
United Kingdom	44 (0) 118 9276201

Other European Countries:

[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

Revised: October 24, 2007

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2008  
Printed in USA, January 18, 2008  
5965-5545E



Agilent Technologies