


Arbitrary Waveform Generator

▶ AWG710



▶ AWG710.

The AWG710 Arbitrary Waveform Generator Delivers World-class Signal Fidelity at 4.0 GS/s to Solve Ever-increasing Measurement Challenges

The AWG710 combines world-class signal fidelity with ultra high-speed mixed signal simulation, a powerful sequencing capability and graphical user interface with flexible waveform editor, to solve the toughest measurement challenges in the disk drive, communications and semiconductor design/test industries.

Standard Waveforms for Communications

ITU-T
STM1E, E5 CEPT, E4, E3, E2, E1

TI.102
STS-3, STS-1, DS4NA, DS3, DS2, DS1/1C/1A

Fibre Channel
FC1063E, FC531E, FC266E, FC133E

SDH/SONET
OC-48/STM-16, OC-36, OC-24, OC-18,
OC-12/STM-4, OC-3/STM-1, OC-1/STM-0

Other
D2, D1, FDD-1, 100Base-TX, Gigabit Ethernet

▶ Features & Benefits

4.0 GS/s Sample Rate
Simulates Real-world Signals
Up To 2.0 GHz

2 Markers With 1.6 pS_{RMS} Jitter
Deliver Ultra-stable Timing to
the Device-under-test (DUT)

16 M or 32 M Point Record
Length Provide Longer
Serial or Rotational Media
Data Streams

8-bit Vertical Resolution for
Precise Signal Replication

Analog Bandwidth to 2 GHz
(Option 02, Calculated Based
on Rise Time) Provides the
Highest Signal Fidelity of All
High-speed AWGs

EZ Function Generator Mode
Allows Quick Creation and
Edit of Sine, Square, Triangle,
Ramp, Pulse and DC
Waveforms

Waveform Quick Editor
with 300 fs Edge Timing
Resolution Delivers Output
Edge Control with Near
Real-time Precision

Real-time Sequencing
Creates Infinite Waveform
Loops, Jumps, Patterns
and Conditional Branches

GPIO and LAN (10/100Base-T)
Interfaces

▶ Applications

Disk Drive Read/Write
Design and Test

Communications Design
and Test
– Arbitrary IF Baseband Signals
– Standard Waveforms for
Communications

Pulse Generation
– High-speed, Low-jitter
Data and Clock Source

Mixed Signal Design and Test

Real-world Simulations
– Corruption and Enhancement
of Ideal Waveforms
– Timing and Amplitude
Signal Impairments
– Waveforms Imported from
MathCad, MATLAB, Excel
and Others


COMPUTING

COMMUNICATIONS

VIDEO

Arbitrary Waveform Generator

▶ AWG710



▶ The built-in signal applications enable you to easily create standard waveforms for disk drive, communications and semiconductor applications. A disk drive read channel is shown here.

▶ Characteristics

Arbitrary Waveforms

Waveform Length – 960 to 16,200,000 points (or 32,400,000 points, option 01) in multiples of four.

Sequence Length – 1 to 8,000 steps.

Sequence Repeat Counter – 1 to 65,536 or infinite.

Function Generator Waveforms

Operation Mode – Continuous mode only.

Waveform Shape – Sine, Triangle, Square, Ramp, Pulse or DC.

Frequency – 1.000 Hz to 400.0 MHz.

Amplitude

Range: $0.020 V_{p-p}$ to $2 V_{p-p}$ into 50Ω .
Resolution: 1 mV.

Offset

Range: $-0.500 V$ to $+0.500 V$ into 50Ω .
Resolution: 1 mV.

DC Level

Range: $-0.500 V$ to $+0.500 V$ into 50Ω .
Resolution: 1 mV.

Polarity

Normal, Invert.

Duty Cycle

Range: 0.1% to 99.9%, Pulse waveform only.

Resolution:

1.000 Hz to 4.000 MHz: 0.1% step.
4.001 MHz to 20.00 MHz: 0.5% step.
20.01 MHz to 40.00 MHz: 1% step.
40.01 MHz to 80.00 MHz: 2% step.
80.01 MHz to 100.0 MHz: 2.5% step.
100.1 MHz to 160.00 MHz: 4% step.
160.1 MHz to 200.0 MHz: 5% step.
200.1 MHz to 400.0 MHz: 10% step.

Marker Out

Marker1 Pulse Width:
Hi/Lo: 20%/80% of Period.

Marker2 Pulse Width:
Hi/Lo: 50%/50% of Period, except 100.1 MHz to 160.0 MHz.
Hi/Lo: 52%/48% of Period, at 100.1 MHz to 160.0 MHz.

Marker Level:

Hi Level: 2 V into 50Ω .
Lo Level: 0 V into 50Ω .

Clock Generator

Sampling Frequency – 50.000000 kHz to 4.0000000 GHz.

Resolution – 8 digits.

Internal Clock – Accuracy: ± 1 ppm.

Phase Noise – (data clock is 1/4th of the output sample rate)

At 1 GS/s, 10 kHz offset: -80 dBc/Hz.
At 1 GS/s, 100 kHz offset: -100 dBc/Hz.

Operating Modes

Continuous – Waveform is iteratively output. If a sequence is defined, the sequence order and repeat functions are applied.

Triggered – Waveform is output only once when an external, internal, GPIB, LAN or manual trigger is received.

Gated – Waveform begins output when gate is true and resets to beginning when false.

Enhanced – Waveform is output as defined by the sequence.

Internal Trigger Generator

Internal Trigger Rate

Range: 1.0 μs to 10.0 s.
Resolution: 3 digits, 0.1 μs minimum.
Accuracy: $\pm 0.1\%$.

Main Output

Output Signal – Complementary; CH1 and channel inverse.

Digital to Analog Converter

Resolution: 8-bits.
Differential Non-linearity: $\pm 1/2$ -LSB.
Integral Non-linearity: ± 1 -LSB.

Output Connector – Front Panel SMA.

Normal Out*1

Amplitude

Output Voltage: $-1.5 V$ to $+1.5 V$ into 50Ω .
Amplitude: 20 mV to 2.0 V into 50Ω .

Resolution: 1 mV.

DC Accuracy: $\pm(2.0\%$ of Amplitude + 2 mV) at offset = 0 V.

Offset

Range: $-0.500 V$ to $+0.500 V$ into 50Ω .

Resolution: 1 mV.

Accuracy: $\pm 1.5\%$ of offset ± 10 mV at 20 mV amplitude.

Pulse Response – (–1 and 1 waveform data, 0 V offset, through filter at $1 V_{p-p}$, clock 1 GS/s):

Rise Time: (10% to 90%): ≤ 480 ps.

Fall Time: (10% to 90%): ≤ 480 ps.

Aberrations: At $1.0 V_{p-p}$.

Amplitude: $\pm 6\%$.

Flatness: (after 20 ns from rise/fall edge) $\pm 3\%$.

Sine Wave Characteristics (4.0 GS/s clock, 32 waveform points, 125 MHz signal frequency, 1.0 V amplitude, 0 V offset, through filter) –

Harmonics: ≤ -40 dBc, DC to 1000 MHz.

Noise: ≤ -50 dBc, DC to 1000 MHz.

Phase Noise: ≤ -85 dBc/Hz at 10 kHz offset.

Filter*1

Type – 20, 50, 100, 200 MHz Bessel low-pass.

Rise Time (10% to 90%) – 20 MHz, 17 ns; 50 MHz, 7.0 ns; 100 MHz, 3.7 ns; 200 MHz, 2.0 ns.

Group Delay – 20 MHz, 18 ns; 50 MHz, 8 ns; 100 MHz, 4.7 ns; 200 MHz, 3 ns.

Direct D/A Out*1

Amplitude – $20 mV_{p-p}$ to $1.0 V_{p-p}$ into 50Ω .

Resolution – 1 mV.

DC Accuracy – $\pm(2\%$ of Amplitude + 2 mV).

Offset – no function.

DC Offset Accuracy – 0 V ± 10 mV at 20 mV amplitude (waveform data = 0).

Pulse Response (–1 and 1 waveform data, at $0.5 V_{p-p}$) –

Rise Time (10% to 90%): ≤ 280 ps.

Fall Time (10% to 90%): ≤ 280 ps.

Output Impedance – 50Ω .

*1 Option 02 eliminates the ability to switch between normal and direct D/A out, as well as filter and offset control.

Extended Bandwidth Output (Option O2)**Amplitude** – 500 mV_{p-p} to 1.0 V_{p-p} into 50 Ω.**Resolution** – 1 mV.**DC Accuracy** – ±(2.0% of amplitude + 2 mV).**Offset** – No function.**Filter** – No function.**DC Offset Accuracy** – 0 V ± 10 mV (waveform data = 0).**Pulse Response** – (–1 and 1 waveform data, at 1.0 V_{p-p}).**Rise Time** – (10% to 90%): ≤ 175 ps.**Fall Time** – (10% to 90%): ≤ 175 ps.**Output Impedance** – 50 Ω.**Auxiliary Outputs****Marker****Number** – 2 (complementary).**Level** –Hi/Lo: –1.1 V to 3.0 V into 50 Ω (Max. 2.5 V_{p-p}).–2.2 V to 6.0 V into 1 MΩ. (Max. 2.5 V_{p-p}).Amplitude: 2.5 V_{p-p} max. into 50 Ω.**Resolution** – 0.05 V.**DC Accuracy** – Within ±0.1 V ± 5% of setting into 50 Ω.**Rise/Fall Time (20% to 80%)** – 150 ps (2 V_{p-p}, Hi +1 V, Lo –1 V) into 50 Ω.**Period Jitter** –At 4 GS/s 1.6 pS_{RMS}.At 2 GS/s 1.9 pS_{RMS}.At 1 GS/s 2.5 pS_{RMS}.**Cycle-to-Cycle Jitter** –At 4 GS/s 3.1 pS_{RMS}.At 2 GS/s 3.2 pS_{RMS}.At 1 GS/s 3.1 pS_{RMS}.**Delay (between analog output and marker output) -**Marker Level: 2 V_{p-p} (Hi +1 V/Lo –1 V).Analog Output: At 1 V_{p-p}.

Normal Output: 3 ns (Offset 0 V, Filter = "Through.")

Direct Output, –500 ps.

Marker Skew – 70 ps (typical).**Connector** – Front-panel SMA.**10 MHz Reference Clockout****Amplitude** – 1.2 V_{p-p} into 50 Ω. Max 2.5 V_{p-p} open.**Impedance** – 50 Ω, AC coupling.**Connector** – Rear-panel BNC.**1/4 Clock Out****Level** – ECL 100 K compatible.**Period Jitter** –At 4 GS/s 2.6 pS_{RMS}.At 2 GS/s 2.4 pS_{RMS}.At 1 GS/s 1.9 pS_{RMS}.**Cycle-to-Cycle Jitter** –At 4 GS/s 4.8 pS_{RMS}.At 2 GS/s 3.7 pS_{RMS}.At 1 GS/s 3.1 pS_{RMS}.**Connector** – Rear-panel BNC.**Trigger In**

Impedance: 1 kΩ or 50 Ω.

Polarity: POS or NEG.

Connector: Rear-panel BNC.

Input Voltage Range –

1 kΩ: ±10 V.

50 Ω: ±5 V.

Threshold –

Level: –5.0 V to 5.0 V.

Resolution: 0.1 V.

Accuracy: ±5% of level + 0.1 V.

Trigger Mode –

Minimum Pulse Width: 10 ns, 0.2 V amplitude.

Trigger Holdoff: ≥109.5 clocks + 500 ns.

Delay to Analog Out: 211.5 clocks + 17 ns (Normal

Output, Filter "Through").

Gate Mode –

Minimum Pulse Width (0.2 V amplitude): 1152 clocks + 10 ns.

Gate Hold Off: ≤1920 clocks + 20 ns.

Delay to Analog Out: 1355 to 1499.5 clocks + 9 ns

(Normal Output, Filter "Through").

Event Trigger Input –

Number of Events: 4-bits.

Input Signals: 4 event bits, strobe.

Threshold: TTL level.

Maximum Input: 0 V to +5 V (DC + peak AC).

Impedance 1 kΩ, pull-up to +3.3 V.

Connector: Rear-panel 9-Pin D-sub.

Enhanced Mode –

Minimum Pulse Width: 320 clocks + 10 ns.

Event Hold Off: ≤896 clocks + 20 ns.

Delay to Analog Out (Jump timing: Async):

Strobe: ON, 1627.5 clocks + 7 ns.

Strobe: OFF, 1883.5 clocks + 5 ns.

Event Input to Strobe Input:

Setup Time: 192 clocks + 10 ns.

Hold Time: 192 clocks + 10 ns.

Reference 10 MHz Clock IN –Input Voltage Range: 0.2 V to 3.0 V_{p-p}, ±10 V maximum.

Impedance: 50 Ω, AC coupled.

Frequency Range: 10 MHz ±0.1 MHz.

Connector: Rear-panel BNC.

General Characteristics**Display** – Color TFT LCD.**Display Area** – Horizontal: 13.06 cm (5.14 in.),

Vertical: 9.70 cm (3.81 in.)

Resolution – 640x480.**Data Storage****Internal Hard Disk** – 10.0 GB.**Flash Disk** – 256 MB.**Floppy Disk** – 3.5", 1.44 MB.**Environment****Temperature** –

Operating: 10 °C to +40 °C.

Nonoperating: –20 °C to +60 °C.

Humidity –

Operating: 20% to 80%.

Nonoperating: 5% to 90%.

Altitude (Hard Disk Restriction)-

Operating: Up to 3,000 m (10,000 ft.).

Nonoperating: Up to 12,000 m (40,000 ft.).

Random Vibration –Operating: 0.27 G_{RMS}, 5 Hz to 500 Hz, 10 minutes.Nonoperating: 2.28 G_{RMS}, 5 Hz to 500 Hz, 10 minutes.**Shock** – Nonoperating: 294 m/s² (30 G), half-sine, 11 ms duration (three times each axis, in each direction, 18 total).**EMC Compliance** – EC Council Directive 89/336/EEC (EC-92), AS/NZS2064-1/2.**Safety** – UL 3111-1, CSA C22.2 No. 1010.1, EN61010-1, IEC61010-1.

Arbitrary Waveform Generator

▶ AWG710

Power Supply

Rating – 100 to 240 VAC.

Range – 90 to 250 VAC.

Maximum Power and Current – 220 VA and 5 A.

Frequency – 48 to 63 Hz.

Physical Characteristics

Dimensions	mm	in.
Height	193	7.60
Width	433	17.05
Depth	508	20.00
Weight	kg	lbs.
Without package	14.1	31.10
With package	24.5	54.00

Interfaces – GPIB, Ethernet: 10/100Base-T, RJ-45.

PC Keyboard – 6-Pin mini-DIN, rear.

▶ Ordering Information

AWG710

4.0 GS/s, 8-bit, 16 M point, single-channel arbitrary waveform generator.

Includes: User manual (070-A828-00), programmer's manual (070-A829-00), GPIB programming examples (062-A258-00), sample waveform library disk (062-A271-00), performance verification (062-A273-00), Certificate of Calibration (no charge), Arb-Link™ software utility (062-A270-00), 50 Ω SMA male terminators (2) (015-1022-01), power cable. Please specify power plug when ordering.

Options

Opt. 01 – 32 M points waveform memory.

Opt. 02 – Extends analog bandwidth to 2 GHz (calculated based on rise time).

Opt. 10 – Flash disk and standby switch (alternative for standard hard disk drive).

Opt. 1R – Rackmount.

Service

Opt. C3 – Calibration Service 3 years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 years (with Option C3).

Opt. R3 – Repair Service 3 years.

Recommended Accessories

Service Manual – Order 070-A830-00.

Protective Cover – Order 200-3696-01.

Power Cord Options

Opt. A0 – U.S. plug, 115 V, 60 Hz.

Opt. A1 – Euro plug, 220 V, 50 Hz.

Opt. A2 – UK plug, 240 V, 50 Hz.

Opt. A3 – Australian plug, 240 V, 50 Hz.

Opt. A5 – Swiss plug, 220 V, 50 Hz.

Opt. A99 – No power cord.

Opt. AC – China plug, 50 Hz.

Software

Arb-Link – (062-A270-01) PC-based waveform creation utility.

Warranty

One year parts and labor.

Contact Tektronix:

ASEAN / Australasia / Pakistan (65) 6356 3900

Austria +43 2236 8092 262

Belgium +32 (2) 715 89 70

Brazil & South America 55 (11) 3741-8360

Canada 1 (800) 661-5625

Central Europe & Greece +43 2236 8092 301

Denmark +45 44 850 700

Finland +358 (9) 4783 400

France & North Africa +33 (0) 1 69 86 80 34

Germany +49 (221) 94 77 400

Hong Kong (852) 2585-6688

India (91) 80-2275577

Italy +39 (02) 25086 1

Japan 81 (3) 3448-3010

Mexico, Central America & Caribbean 52 (55) 56666-333

The Netherlands +31 (0) 23 569 5555

Norway +47 22 07 07 00

People's Republic of China 86 (10) 6235 1230

Poland +48 (0) 22 521 53 40

Republic of Korea 82 (2) 528-5299

Russia, CIS & The Baltics +358 (9) 4783 400

South Africa +27 11 254 8360

Spain +34 (91) 372 6055

Sweden +46 8 477 6503/4

Taiwan 886 (2) 2722-9622

United Kingdom & Eire +44 (0) 1344 392400

USA 1 (800) 426-2200

USA (Export Sales) 1 (503) 627-1916

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Updated 20 September 2002

Our most up-to-date product information is available at:
www.tektronix.com



Copyright © 2002, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

11/02 HB/XBS

76W-14865-2