

# DC Power Supplies

## Tektronix PWS2000 Series Data Sheet



### Features & Benefits

#### Key Performance Specifications

- Linear Regulation
- Up to 72 V Output Voltage
- 0.05% Basic Voltage Accuracy
- 0.2% Basic Current Accuracy
- 10 mV / 10 mA Programming Resolution
- Less than 3 mV<sub>p-p</sub> Ripple and Noise

#### Available Functions and Features

- Bright Display
- 20 User-defined Setup Memories
- Direct Parameter Entry using Numeric Keypad
- Vary Voltage or Current in User-selectable Steps

#### 3-year Warranty

## Generate the Voltage or Current You Need

With wide current and voltage ranges, plus 10 mA and 10 mV resolution, the PWS2000 Power Supply Series satisfies a wide variety of applications. Low-noise linear regulation and 0.05% voltage accuracy provide the clean, accurate power you need at a price you can afford.

## Prevent Damaged Circuits and Lost Test Time

The numeric keypad makes it easy to specify a precise current limit before you start your test. You can also specify a maximum output voltage, which will prevent accidental voltage settings above the specified maximum. A user-definable password allows you to lock the front panel to prevent unwanted adjustments during critical tests.

## Designed to Make Your Work Easier

The PWS2000 Power Supply Series is designed with the ease-of-use and familiar operation you expect from Tektronix.

### Intuitive Operation

The direct-entry numeric keypad makes it easy to enter precise voltage and current values. Up/Down controls, with variable step-size, allow you vary output parameters in an increment size you choose.

### Bright Display

A bright vacuum fluorescent display with large digits provides excellent readability at a distance, at an angle, or under dim lighting conditions.

### Setup Memories

You can save your instrument settings in one of the 20 internal memory locations by simply pressing the Save button. Each time you want to recall that setting, just push the Recall button and choose the desired preset.

## Performance You Can Count On

In addition to industry-leading service and support, the PWS2000 Power Supply Series comes backed with a three-year standard warranty.

## Characteristics

### Electrical

Specifications	PWS2185	PWS2323	PWS2326	PWS2721
DC Output Rating				
Voltage	0 to 18 V	0 to 32 V	0 to 32 V	0 to 72 V
Current	0 to 5 A	0 to 3 A	0 to 6 A	0 to 1.5 A
Load Regulation				
Voltage	≤0.02% + 5 mV	≤0.02% + 5 mV	≤0.04% + 6 mV	≤0.02% + 4 mV
Current	≤0.1 % + 2 mA typical			
Line Regulation				
Voltage	≤0.1 % + 5 mV			
Current	≤0.1 % + 2 mA typical			
Ripple and Noise (20 Hz to 7 MHz)				
Voltage	≤1 mV <sub>RMS</sub> / 3 mV <sub>P-P</sub>			
Current	≤5 mA <sub>RMS</sub>			
Setting Resolution				
Voltage	10 mV			
Current	10 mA			
Setting Accuracy, (25 °C ± 5 °C)				
Voltage	≤0.05% + 10 mV			
Current	≤0.2 % + 10 mA			
Readback Resolution				
Voltage	10 mV	<20 V: 10 mV ≥20 V: 100 mV		
Current	10 mA			
Readback Accuracy, (25 °C ± 5 °C)				
Voltage	≤0.05% + 15 mV	<20 V: ≤0.05% + 15 mV ≥20 V: ≤0.05% + 120 mV		
Current	≤0.1 % + 15 mA			

**Display**

Vacuum fluorescent display.

**Memory**

20 setup memories.

**Power Source**

Characteristic	Description
110 V AC Setting	99 V <sub>RMS</sub> to 132 V <sub>RMS</sub>
220 V AC Setting	198 V <sub>RMS</sub> to 264 V <sub>RMS</sub>
Frequency	47 Hz to 63 Hz
Power Consumption	
PWS2185/2323/2721	250 VA
PWS2326	400 VA

**Physical Characteristics**

Dimension	mm	in.
Height	106	4.2
Width	256	10.0
Depth	383	15.0
Weight	kg	lb.
PWS2185	5.6	12.3
PWS2323/2326/2721	6.7	14.8

**Environmental and Safety**

Characteristic	Description
Temperature	
Operating	0 °C to 40 °C
Storage	-20 °C to 70 °C
Warm up	20 minutes to full uncertainty specifications
Relative Humidity (Noncondensing)	
Operating and storage	5% to 95% relative humidity (% RH) at up to 40 °C, noncondensing
Storage	5% to 95% RH at up to 40 °C, noncondensing 5% to 60% RH above 40 °C to 70 °C, noncondensing
Altitude	
Operating	2,000 meters
Storage	4,000 meters
Electromagnetic Compatibility	European Union: EN 55011, Class A; IEC 61000-3-2; IEC 61000-3-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 USA: FCC, CFR Title 47, Part 15, Subpart B, Class A Australia: EMC Framework, demonstrated per Emission Standard AS/NZS 2064 (Industrial, Scientific, and Medical Equipment)
Safety	European Union: Low Voltage directive 2006/95/EC; EN61010-1 2001 USA: Nationally recognized testing laboratory listing UL61010-1-2004 Canada: CAN/CSA C22.2 No. 61010-1 2004

**Warranty**

Three years.

**Ordering Information****Models**

Model	Description
PWS2185	DC Power Supply, 18 V, 5 A
PWS2323	DC Power Supply, 32 V, 3 A
PWS2326	DC Power Supply, 32 V, 6 A
PWS2721	DC Power Supply, 72 V, 1.5 A

**PWS2000 Includes:** Power supply, line cord, user manual, Traceable Certificate of Calibration, and documentation CD (includes user manuals and technical reference).

Please specify power plug and preferred language option when ordering.

**Instrument Options****Power Plug Options**

Option	Description
A0	North America
A1	Universal Euro
A2	United Kingdom
A3	Australia
A5	Switzerland
A10	China
A11	India
A12	Brazil

**Language Options**

Option	Description
L0	English
L1	French
L2	Italian
L3	German
L4	Spanish
L6	Portuguese
L7	Simplified Chinese
L8	Traditional Chinese
L9	Korean
L10	Russian

**Service Options**

Option	Description
C3	Calibration Service 3 Years
C5	Calibration Service 5 Years
CA1	Provides a single calibration event, or coverage for the designated calibration interval, whichever comes first
D1	Calibration Data Report
D3	Calibration Data Report 3 Years (with Option C3)
D5	Calibration Data Report 5 Years (with Option C5)
R5	Repair Service 5 Years

**Contact Tektronix:**

**ASEAN / Australasia** (65) 6356 3900  
**Austria** 00800 2255 4835\*  
**Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777  
**Belgium** 00800 2255 4835\*  
**Brazil** +55 (11) 3759 7600  
**Canada** 1 800 833 9200  
**Central East Europe, Ukraine, and the Baltics** +41 52 675 3777  
**Central Europe & Greece** +41 52 675 3777  
**Denmark** +45 80 88 1401  
**Finland** +41 52 675 3777  
**France** 00800 2255 4835\*  
**Germany** 00800 2255 4835\*  
**Hong Kong** 400 820 5835  
**India** 000 800 650 1835  
**Italy** 00800 2255 4835\*  
**Japan** 81 (3) 6714 3010  
**Luxembourg** +41 52 675 3777  
**Mexico, Central/South America & Caribbean** (52) 56 04 50 90  
**Middle East, Asia, and North Africa** +41 52 675 3777  
**The Netherlands** 00800 2255 4835\*  
**Norway** 800 16098  
**People's Republic of China** 400 820 5835  
**Poland** +41 52 675 3777  
**Portugal** 80 08 12370  
**Republic of Korea** 001 800 8255 2835  
**Russia & CIS** +7 (495) 7484900  
**South Africa** +41 52 675 3777  
**Spain** 00800 2255 4835\*  
**Sweden** 00800 2255 4835\*  
**Switzerland** 00800 2255 4835\*  
**Taiwan** 886 (2) 2722 9622  
**United Kingdom & Ireland** 00800 2255 4835\*  
**USA** 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 25 May 2010

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tektronix.com](http://www.tektronix.com)



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

15 Oct 2010

3GW-25620-0

