

Lifetime Warranty!

Keep your Fluke meter
up and running

For 20, 70 & 80 Series
DMMs Only

Fluke 73III Multimeter



Features

- Volts, ohms, continuity, diode test
- 10 amp current range
- Touch Hold® to capture readings
- 10 MΩ input impedance, analog bar graph
- Sleep mode

Specifications

Basic Accuracy (\pm % of reading)			
Function	Ranges	Accuracy	Best Resolution
DC Voltage	320 mV -1000V	0.3%	0.1 mV
AC Voltage	3.2V -1000V	2%	1 mV
DC Current	10A	1.5%	0.01 mA
AC Current	10A	2.5%	0.01 mA
Resistance	320Ω - 32 MΩ	0.5%	0.1Ω

Safety

600V, AC/DC maximum voltage between any terminal and earth ground. Conforms to CAT II 600V per ANSI/ISA-S82.01-94, EN 61010-1: 1993, CSA C22.2 No. 1010.1-92. Protected from overvoltage transients to 4 kV

Surge protection

4 kV peak per IEC 1010.1-92.

Fuse protection

630 mA, 250V Min interrupt rating 1500Am IEC 127-1. 11A, 1000V AC/DC, Min interrupt rating 17kA.

Warranty

Lifetime (Meter)
1 year (Accessories)

Included with your Fluke 73III Analog Digital Multimeter

Fluke 73III Analog Digital Multimeter
TL75 right-angle test leads
C70 Yellow Holster
9V battery
Instruction sheet for industrial use

The Fluke 73III gives you basic multimeter features, plus a 10 Amp current range.