




FLIR B200

B-Series InfraRed Camera (240 x 180 IR Resolution)

With on board Visual Camera, Picture-in-Picture Fusion, Touch Screen LCD & Interchangeable Lens

- 0.07°C @ 30°C Thermal Sensitivity
- Bright Video Lamp
- Annotate Images with Voice
- Picture-in-Picture Fusion
- 3.5" Touch-Screen LCD Display
- Convenient 120° rotating lens
- 2X Continuous Zoom
- Analysis/Reporting Software included



Multifunction Touch Screen Picture-in-Picture (PIP) Fusion Differential Temperature



FLIR B200 Features

- **High Resolution IR Images** — 43,200 pixels (240 x 180) Infrared resolution
- **Visible Light Digital Camera** — 3.1MP resolution with flash provides sharp images regardless of lighting conditions
- **2X Continuous Zoom** — Zoom with auto/manual focus
- **Rotating Lens** — Rotating lens detents up to 120° for easy viewing angle
- **Insulation Alarm** — Detects areas that don't fulfill the insulation requirements
- **Dew Point Alarm** — Displays areas with risk of surface condensation where mold growth could occur
- **Scalable Picture in Picture (PIP) Fusion** — Displays thermal image super-imposed over a digital image
- **Video Lamp** — Allows the visual camera and fusion to be used in poorly lit environments
- **Temperature Range** — From -4 to 248°F (-20 to 120°C) targeting insulation, HVAC, and building applications; Optional higher temperature up to 2192°F/1200°C available
- **± 2% Accuracy** — reliable temperature measurement
- **Thumbnail Image Gallery** — Allows quick search of stored images
- **Li-Ion Rechargeable Battery** — lasts >4hrs continuous use; replaceable
- **Copy to USB** — Easy upload of a single image or a folder from the camera to a USB memory stick
- **Laser LocatIR™ Pointer** — Pinpoints a reference spot with a laser and aligns a marker to it on the image
- **IR Window Correction** — Menu settings allow you to account for transmission loss through IR windows
- **Voice Comment Recording** — on images & can be integrated onto report
- **Wireless Communication** — Bluetooth® Transmitter with METERLiNK™
- **Includes** — SD Memory Card (stores >1000 Radiometric JPEG images), two rechargeable batteries, 2-bay battery charger, QuickReport software, USB Mini-B cable, Bluetooth® USB micro adapter, sun shield, stylus pen, headset, camera lens cap, and hard transport case
- **Interchangeable Optics** — Optional 6°, 15°, 45°, 90°, Close up: 100, 50, 25µm, easily attach to the camera



Warranty extended to 2 years when the camera is registered

Applications



Water Damage — Water leak on ceiling, gutter, and roof top


Insulation — Energy Loss, Home Inspection, and HVAC

Software Packages

QuickReport™ PC software enables users to Organize, Analyze and Create Reports with FLIR Cameras.

FLIR BuildIR Software package specifically designed to carry out advanced analysis of building structures. It is used to analyze images taken with an infrared camera, and create inspection reports based on these images.

FLIR Reporter Ver. 8.5 is a powerful software for creating compelling and professional, fully customized, easy-to-interpret reports in a standard MS Word Document. You can create a report by simply Dragging and Dropping your images on a desktop icon or using the Wizards to guide you step-by-step through the process. The saved document is a 'live' report with full access to the analysis tools and temperature measurement data. The reports can be multi-page and include all of your IR inspection data -infrared and visual images, temperature measurements, voice comments and text notes.



Panorama Function

This unique function allows you to conveniently piece together normal sized images to create one large image for a wide angle view of the area being measured by using FLIR BuildIR or Reporter Software package



METERLiNK frees the Thermographer from the manual process of collecting field data



Infrared cameras quickly locate moisture related problems



Collecting moisture readings on damaged surfaces and associating them with regions on an infrared image can be a complicated and cumbersome process



Manual data collection is time-consuming and prone to errors. METERLiNK eliminates this problem by allowing the thermographer to quickly take moisture readings on a damaged surface and associate those readings with the corresponding targets stored in an infrared image



FLIR ThermaTrak™

If your IR camera is lost or stolen, ThermaTrak can help you track where it is.

FLIR B200 Specifications

Features

Temperature range	-4°F to 248°F (-20°C to 120°C); Optional Higher Temperature available
Image Storage	1000 radiometric JPEG images (SD card memory)

Imaging Performance / Image Presentation

Frame Rate	9Hz
Field of view/min focus distance	25° x 19°/1.31ft (0.4m)
Focus	Manual/Automatic
Thermal sensitivity (N.E.T.D)	<0.07°C at 30°C
Detector Type - Focal plane array (FPA) uncooled microbolometer	240 x 180 pixels
Spectral range	7.5 to 13µm
Display	Built-in touch-screen 3.5" color LCD
Image modes	Thermal/Visual/Picture-in-Picture Fusion
Image annotation	Voice (60 sec)
Lens	25° (optional 6°, 15°, 45°, 90°, Close up 100, 50, 25µm lenses available)
Video Lamp	Bright LED lamp
Laser Classification/Type	Class 2/Semiconductor AlGaInP Diode Laser: 1mW/635nm (red)
Set-up controls	Mode selector, color palettes, configure info to be shown in image, local adaptation of units, language, date and time formats, and image gallery
Measurement modes	5 Spotmeters, 5 Box areas, Isotherm, Auto hot/cold spot, Delta T
Measurement correction	Reflected ambient temperature & emissivity correction
Battery Type/operating time	Li-Ion/ >4 hours, Display shows battery status
Charging system	In camera AC adapter/2 bay charging system
Shock	25G, IEC 68-2-29
Vibration	2G, IEC 68-2-6
Dimensions/Weight	4.2x7.9x4.9" (106x201x125mm)/1.94lbs (0.88kg), including battery
Warranty	2 years (Warranty extended to 2 years when the camera is registered)

Ordering Information

Part Number

45608-0201FLIR B200 Thermal Imaging InfraRed Camera (240x180)

ACCESSORIES*

1196398Li-Ion Rechargeable Battery
1910399AC Adapter Charger (110-240V, U.S. Plug)
1910490Cigarette Lighter Adapter Kit, 12VDC (1.2m cable)
T1976502-Bay Battery Charger including Power Supply (multi plugs)
1124545Camera Pouch Case
T197000High Temperature Option 2192°F/1200°C
T197006High Temperature Option 662°F/350°C
T197613BuildIR Software package
T197717FLIR Reporter Ver. 8.5 Professional
4114887FLIR ThermaTrak™

CERTIFICATION TRAINING

T-BSCCertification in Infrared Building Science per attendee (3.5 Day Class)
ITC-RESNRG-2Thermal Imaging for Residential Energy Audits Training per attendee (2 Day Class)
ITC-RESNRG-4Thermal Imaging for Residential Energy Audits Certification per attendee (4 Day Class)

*Optional Camera Lenses available. Please refer to the Camera Lens Datasheet

Tel: 1.877.744.FLIR | www.extech.com/bseries

Specifications and prices subject to change without notice. Rev. 04/15/10-R1

Copyright © 2010 Extech Instruments Corporation (A FLIR Company). All rights reserved including the right of reproduction in whole or in part in any form.

EXTECH
INSTRUMENTS
A FLIR COMPANY